



## Atóxica Transparente com Espiral Branco e Fio Antiestático

Ideal para sucção e descarga de produtos alimentícios ou grãos. Provida de fios de cobre em sua parede, evita a eletricidade estática. Isenta de Ftalato.

**Temperatura de Trabalho: +5°C ~ +50°C (PVC).**

DIÂMETRO NOMINAL	DIÂMETRO INTERNO	DIÂMETRO EXTERNO	PRESSÃO DE TRABALHO		PRESSÃO DE RUPTURA		VÁCUO	RAIO DE CURVATURA		LANCE
			25°C		25°C			25°C		
pol.	mm	mm	kgf/cm2	lbf/pol2	kgf/cm2	lbf/pol2	mmHg	Trabalho - Mínimo		m
1"	25,0	31,5	8,0	114	24	341	760	495		25 / 50
1.1/4"	31,5	39,0	7,3	104	22	313	760	505		25 / 50
1.1/2"	38,0	46,0	6,7	95	20	284	760	550		25 / 50
1.5/8"	40,0	48,0	6,0	85	18	256	760	750		25 / 50
1.3/4"	45,0	53,8	6,0	85	18	256	760	750		25 / 50
2"	50,0	59,5	6,0	85	18	256	760	770		25 / 50
2.1/2"	62,5	73,0	6,0	85	18	256	760	880		25 / 50
3"	74,5	86,0	5,3	76	16	228	760	1.430		25 / 50
4"	101,2	115,0	5,0	71	15	213	760	1.750		25 / 50
5"	127,0	140,0	2,7	38	8	114	760	2.475		15 / 30
6"	149,0	164,0	2,0	28	6	85	760	2.750		15 / 30



## Transparente con Espiral Blanco y Hilo Antiestático

Ideal para succión y descarga de productos alimenticios o granos. Construida con hilos de cobre en el interior de la pared, evita la electricidad estática. Libre de Ftalato.

**Temperatura de Trabajo: +5°C ~ +50°C (PVC)**

DIÂMETRO NOMINAL	DIÂMETRO INTERNO	DIÂMETRO EXTERNO	PRESIÓN DE TRABAJO		PRESIÓN DE RUPTURA		VACÍO	RADIO DE CURVATURA		LARGO
			25°C		25°C			25°C		
pul.	mm	mm	kgf/cm2	lbf/pol2	kgf/cm2	lbf/pol2	mmHg	Trabajo - Mínimo		m
1"	25,0	31,5	8,0	114	24	341	760	495		25 / 50
1.1/4"	31,5	39,0	7,3	104	22	313	760	505		25 / 50
1.1/2"	38,0	46,0	6,7	95	20	284	760	550		25 / 50
1.5/8"	40,0	48,0	6,0	85	18	256	760	750		25 / 50
1.3/4"	45,0	53,8	6,0	85	18	256	760	750		25 / 50
2"	50,0	59,5	6,0	85	18	256	760	770		25 / 50
2.1/2"	62,5	73,0	6,0	85	18	256	760	880		25 / 50
3"	74,5	86,0	5,3	76	16	228	760	1.430		25 / 50
4"	101,2	115,0	5,0	71	15	213	760	1.750		25 / 50
5"	127,0	140,0	2,7	38	8	114	760	2.475		15 / 30
6"	149,0	164,0	2,0	28	6	85	760	2.750		15 / 30



## Nontoxic Transparent with White Spiral and Anti-static Wire

Ideal for suction and discharge of food products or grains. Copper wiring in inner wall prevents static electricity. Phthalate free.

**Working Temperature: +5°C ~ +50°C (PVC).**

NOMINAL DIAMETER	INTERNAL DIAMETER	EXTERNAL DIAMETER	WORK PRESSURE		BURST PRESSURE		VACUUM	BEND RADIUS		LENGTH
			25°C		25°C			25°C		
inches	mm	mm	kgf/cm	psi	kgf/cm	psi	mmHg	Minimum Working		m
1"	25,0	31,5	8,0	114	24	341	760	495		25 / 50
1.1/4"	31,5	39,0	7,3	104	22	313	760	505		25 / 50
1.1/2"	38,0	46,0	6,7	95	20	284	760	550		25 / 50
1.5/8"	40,0	48,0	6,0	85	18	256	760	750		25 / 50
1.3/4"	45,0	53,8	6,0	85	18	256	760	750		25 / 50
2"	50,0	59,5	6,0	85	18	256	760	770		25 / 50
2.1/2"	62,5	73,0	6,0	85	18	256	760	880		25 / 50
3"	74,5	86,0	5,3	76	16	228	760	1.430		25 / 50
4"	101,2	115,0	5,0	71	15	213	760	1.750		25 / 50
5"	127,0	140,0	2,7	38	8	114	760	2.475		15 / 30
6"	149,0	164,0	2,0	28	6	85	760	2.750		15 / 30

