

Exaustão de Gases – Cinza com Espiral de Aço Mola

Indicada para utilização em exaustão de gases, vapores, e sistemas de ventilação. Excelente flexibilidade e leveza. Taxa de compressão axial de 8:1.

Temperatura de Trabalho: -20°C ~ +100°C (PVC+POLIÉSTER)

DIÂMETRO NOMINAL	DIÂMETRO INTERNO	RAIO DE CURVATURA		LANCE
pol.	mm	Trabalho - Mínimo		m
		25°C	mm	
2"	51,0	26		10
3"	76,0	38		10
4"	102,0	51		10
5"	127,0	64		10
6"	152,0	76		10
8"	203,0	102		10



Extracción de Gases – Gris con Espiral de Acero Tipo Resorte

Indicada para uso en exhaustos de gases, vapores y sistemas de ventilación. Excelente flexibilidad y liviano. Relación de compresión axial de 8:1 a depender del diámetro.

Temperatura de Trabajo: -20°C ~ +100°C (PVC+POLIÉSTER)

DIÂMETRO NOMINAL	DIÂMETRO INTERIOR	RADIO DE CURVATURA		LARGO
pul.	mm	Trabajo - Mínimo		m
		25°C	mm	
2"	51,0	26		10
3"	76,0	38		10
4"	102,0	51		10
5"	127,0	64		10
6"	152,0	76		10
8"	203,0	102		10



Gas Exhaust – Grey with Spring Steel Spiral

Used in civil and naval conditioning plants, ventilation systems, suction of fumes, vapours, powders and gas. Possibility axial compression 8:1.

Working Temperature: -20°C ~ +100°C (PVC+POLYESTER)

NOMINAL DIAMETER	INTERNAL DIAMETER	RADIUS DIAMETER	LENGTH
inches	mm	Working - Minimum	
		25°C	mm
2"	51,0	26	10
3"	76,0	38	10
4"	102,0	51	10
5"	127,0	64	10
6"	152,0	76	10
8"	203,0	102	10

