MANGUEIRA **KANASPRAY**

Com Trama - Pivô de Irrigação - Preta

Mangueira de PVC reforçada com fios sintéticos utilizada em pivôs de irrigação. Leve e flexível, possui boa resistência à abrasão e intempéries.

Temperatura de Trabalho:+5°C ~ +50°C (PVC).

DIÂMETRO NOMINAL	DIÂMETRO INTERNO	DIÂMETRO EXTERNO	PRESSÃO DE TRABALHO		PRESSÃO DE RUPTURA		LANCE
			25°C				
pol.	mm	mm	kgf/cm²	lbf/pol²	kgf/cm²	lbf/ pol²	m
3/4"	20,5	25,5	7	100	21	300	50

Con Trama – Pivote de Riego – Negra

Manguera de PVC reforzada con hilos sintéticos utilizada en pivotes de riego. Ligero y flexible, posee buena resistencia a la abrasión e intemperie.

Temperatura de Trabajo: +5°C ~ +50°C (PVC).

DIÁMETRO NOMINAL	DIÁMETRO INTERIOR	DIÁMETRO EXTERIOR	PRESIÓN DE TRABAJO		PRESIÓN DE RUPTURA		LARGO
			25°C				
pul.	mm	mm	kgf/cm2	lbf/pul²	kgf/cm2	lbf/pul²	m
3/4"	20,5	25,5	7	100	21	300	50

Braided – Irrigation Pivot – Black

Reinforced PVC hose with synthetic threads used in irrigation pivots. Lightweight and flexible, it has good resistance to abrasion and bad weather.

Working Temperature:+5°C ~ +50°C (PVC).

NOMINAL DIAMETER	INTERNAL DIAMETER	EXTERNAL DIAMETER	WORK PRESSURE		BURST PRESSURE		LENGTH
			25°C				
inches	mm	mm	kgf/cm2	psi	kgf/cm2	psi	m
3/4"	20,5	25,5	7	100	21	300	50

Kanaflex®
comercialmangueiras@kanaflex.com.br
(11) 4785-2100