



Com Trama - Pivô de Irrigação - Preta

Mangueira de PVC reforçada com fios sintéticos utilizada em pivôs de irrigação. Leve e flexível, possui boa resistência à abrasão e intempéries.

Temperatura de Trabalho: +5°C ~ +50°C (PVC).

DIÂMETRO NOMINAL	DIÂMETRO INTERNO	DIÂMETRO EXTERNO	PRESSÃO DE TRABALHO		PRESSÃO DE RUPTURA		LANCE
				25°C			
pol.	mm	mm	kgf/cm ²	lbf/pol ²	kgf/cm ²	lbf/ pol ²	m
3/4"	20,5	25,5	7	100	21	300	50



Con Trama - Pivote de Riego - Negra

Manguera de PVC reforzada con hilos sintéticos utilizada en pivotes de riego. Ligero y flexible, posee buena resistencia a la abrasión e intemperie.

Temperatura de Trabajo: +5°C ~ +50°C (PVC).

DIÂMETRO NOMINAL	DIÂMETRO INTERIOR	DIÂMETRO EXTERIOR	PRESIÓN DE TRABAJO		PRESIÓN DE RUPTURA		LARGO
				25°C			
pul.	mm	mm	kgf/cm ²	lbf/pul ²	kgf/cm ²	lbf/pul ²	m
3/4"	20,5	25,5	7	100	21	300	50



Braided - Irrigation Pivot - Black

Reinforced PVC hose with synthetic threads used in irrigation pivots. Lightweight and flexible, it has good resistance to abrasion and bad weather.

Working Temperature: +5°C ~ +50°C (PVC).

NOMINAL DIAMETER	INTERNAL DIAMETER	EXTERNAL DIAMETER	WORK PRESSURE		BURST PRESSURE		LENGTH
				25°C			
inches	mm	mm	kgf/cm ²	psi	kgf/cm ²	psi	m
3/4"	20,5	25,5	7	100	21	300	50

