



Azul com Tubo Interno Preto

Indicada para utilização sob grande pressão em sistemas de lava-auto. Excelente flexibilidade, face interna totalmente lisa reduzindo perdas de carga ao longo da linha.

Temperatura de Trabalho: +5°C ~ +50°C (PVC).

DIÂMETRO NOMINAL	DIÂMETRO INTERNO	DIÂMETRO EXTERNO	PRESSÃO DE TRABALHO		LANCE
25°C					
pol.	mm	mm	kgf/cm2	lbf/pol2	m
1/2"	12,7	23,1	68,0	1000	50/100
3/4"	19,1	29,8	52,7	750	50



Azul con Tubo Interno Negro

Para uso a alta presión en sistemas de lavado de coches. Excelente flexibilidad, superficie interior completamente lisa, que reduce la pérdida de carga a lo largo de la línea.

Temperatura de Trabajo: +5°C ~ +50°C (PVC).

DIÁMETRO NOMINAL	DIÁMETRO INTERIOR	DIÁMETRO EXTERNO	PRESIÓN DEL TRABAJO		LARGO
25°C					
pul.	mm	mm	kgf/cm2	lbf/pol2	m
1/2"	12,7	23,1	68,0	1000	50/100
3/4"	19,1	29,8	52,7	750	50



Blue with Black Inner Tube

Hose recommended for high-pressure use in car washer systems. Excellent flexibility, glossy inner wall reduces load losses along the line.

Working Temperature: +5°C ~ +50°C (PVC).

NOMINAL DIAMETER	INTERNAL DIAMETER	EXTERNAL DIAMETER	WORK PRESSURE		LENGTH
25°C					
inches	mm	mm	kgf/cm2	psi	m
1/2"	12,7	23,1	68,0	1000	50/100
3/4"	19,1	29,8	52,7	750	50

