

MANGUEIRA KPU-BOR

Preta com Espiral de Aço Mola

Indicada para condução de ar quente, gases e vapores químicos.

Temperatura de Trabalho: -40°C ~ +125°C (BORR TERMOPL).

DIÂMETRO NOMINAL	DIÂMETRO INTERNO	VÁCUO	RAIO DE CURVATURA	LANCE
pol.	mm	25°C mmHg	Trabalho - Mínimo 25°C mm	m
40	40,0	150	32	20
45	45,0	150	36	20
50*	51,0	150	40	20
60	60,0	127	50	20
65	63,0	127	55	20
70	70,0	127	60	20
75	76,0	127	65	20
80	80,0	120	65	20
90	90,0	120	75	20
100	102,0	97	85	15
110	110,0	90	90	15
120	120,0	75	100	15
125	127,0	75	105	15
130	130,0	60	105	15
140	140,0	60	115	15
150	152,0	60	125	15
160*	160,0	52	130	15
180	180,0	37	150	15
200	203,0	30	165	15
225	228,0	30	185	15
250	254,0	30	210	10
280*	279,0	30	230	10
300*	305,0	22	250	10
350*	356,0	22	300	10
400	406,0	22	350	10

Diâmetros marcados na cor cinza são fornecidas sob consulta



Transparente con Espiral Naranja

Adecuadas para conducir aire caliente (hasta 125°C), gases y vapores químicos.

Temperatura de Trabajo: -40°C ~ +125°C (CAUCHO TERMOPL).

DIÂMETRO NOMINAL	DIÂMETRO INTERIOR	VACUUM	RADIO DE CURVATURA	LARGO
mm	mm	25°C mmHg	Trabajo - Mínimo 25°C mm	m



Transparent with Orange Spiral

Recommended for conduction of hot air up to 125°C (257°F), gases, and chemical fumes.

Working Temperature: -40°C ~ +125°C (THERMOPLASTIC RUBBER).

NOMINAL DIAMETER	INTERNAL DIAMETER	VACUUM	BEND RADIUS	LENGTH
Inches	mm	25°C mmHg	Working - minimum 25°C mm	m

