



Cristal – Transparente

Indicada para condução e manuseio de líquidos de uso industrial. Sua transparência admite visualização do conteúdo interno.

Temperatura de Trabalho: +5°C ~ +50°C (PVC).

| DIÂMETRO NOMINAL | DIÂMETRO INTERNO | DIÂMETRO EXTERNO | ESPESSURA | LANCE |
|------------------|------------------|------------------|-----------|--------|
| pol. | mm | mm | mm | m |
| 1/4" | 6,4 | 8,4 | 1,0 | 50/100 |
| 5/16" | 7,9 | 9,9 | 1,0 | 50/100 |
| 5/16" | 7,9 | 11,9 | 2,0 | 50/100 |
| 3/8" | 9,5 | 11,5 | 1,0 | 50/100 |
| 3/8" | 9,5 | 13,5 | 2,0 | 50/100 |
| 1/2" | 12,7 | 16,7 | 2,0 | 50/100 |
| 5/8" | 15,9 | 19,9 | 2,0 | 50/100 |
| 5/8" | 15,9 | 21,9 | 3,0 | 50/100 |
| 3/4" | 19,0 | 23,0 | 2,0 | 50/100 |
| 3/4" | 19,0 | 26,0 | 3,0 | 50/100 |
| 7/8" | 22,2 | 26,2 | 2,0 | 50/100 |
| 1" | 25,4 | 29,4 | 2,0 | 50/100 |
| 1.1/4" | 31,8 | 36,8 | 2,5 | 25 |
| 1.1/2" | 38,1 | 44,1 | 3,0 | 25 |



Cristal – Transparente

Indicado para conducción y manejo de líquidos en uso industrial. Su transparencia permite la visualización del contenido interno.

Temperatura de Trabajo: +5°C ~ +50°C (PVC).

| DIÂMETRO NOMINAL | DIÂMETRO INTERIOR | DIÂMETRO EXTERIOR | ESPESSOR | LARGO |
|------------------|-------------------|-------------------|----------|--------|
| pol. | mm | mm | mm | m |
| 1/4" | 6,4 | 8,4 | 1,0 | 50/100 |
| 5/16" | 7,9 | 9,9 | 1,0 | 50/100 |
| 5/16" | 7,9 | 11,9 | 2,0 | 50/100 |
| 3/8" | 9,5 | 11,5 | 1,0 | 50/100 |
| 3/8" | 9,5 | 13,5 | 2,0 | 50/100 |
| 1/2" | 12,7 | 16,7 | 2,0 | 50/100 |
| 5/8" | 15,9 | 19,9 | 2,0 | 50/100 |
| 5/8" | 15,9 | 21,9 | 3,0 | 50/100 |
| 3/4" | 19,0 | 23,0 | 2,0 | 50/100 |
| 3/4" | 19,0 | 26,0 | 3,0 | 50/100 |
| 7/8" | 22,2 | 26,2 | 2,0 | 50/100 |
| 1" | 25,4 | 29,4 | 2,0 | 50/100 |
| 1.1/4" | 31,8 | 36,8 | 2,5 | 25 |
| 1.1/2" | 38,1 | 44,1 | 3,0 | 25 |



Crystal – Transparent

Indicated for conducting and handling liquids in industrial use. Its transparency allows visualization of the internal content.

Working Temperature: +5°C ~ +50°C (PVC).

| NOMINAL DIAMETER | INTERNAL DIAMETER | EXTERNAL DIAMETER | THICKNESS | LENGTH |
|------------------|-------------------|-------------------|-----------|--------|
| pol. | mm | mm | mm | m |
| 1/4" | 6,4 | 8,4 | 1,0 | 50/100 |
| 5/16" | 7,9 | 9,9 | 1,0 | 50/100 |
| 5/16" | 7,9 | 11,9 | 2,0 | 50/100 |
| 3/8" | 9,5 | 11,5 | 1,0 | 50/100 |
| 3/8" | 9,5 | 13,5 | 2,0 | 50/100 |
| 1/2" | 12,7 | 16,7 | 2,0 | 50/100 |
| 5/8" | 15,9 | 19,9 | 2,0 | 50/100 |
| 5/8" | 15,9 | 21,9 | 3,0 | 50/100 |
| 3/4" | 19,0 | 23,0 | 2,0 | 50/100 |
| 3/4" | 19,0 | 26,0 | 3,0 | 50/100 |
| 7/8" | 22,2 | 26,2 | 2,0 | 50/100 |
| 1" | 25,4 | 29,4 | 2,0 | 50/100 |
| 1.1/4" | 31,8 | 36,8 | 2,5 | 25 |
| 1.1/2" | 38,1 | 44,1 | 3,0 | 25 |

