



Vácuo Ar – Preta com Espiral Cinza

Indicada para sopradores, ventilação industrial, exaustores industriais, coletores de pó, ar condicionado para escritórios e coifas de exaustão.

Temperatura de Trabalho: +5°C ~ +50°C (PVC).

DIÂMETRO NOMINAL	DIÂMETRO INTERNO	DIÂMETRO EXTERNO	VÁCUO	RADIO DE CURVATURA	LANCE
Trabalho - Mínimo					
pol.	mm	mm	mm	mmHg	25°C mm
1.1/4"	32	31.5	37.5	400	70
1.1/2"*	38	38	45.5	400	90
2.1/2"	65	62.5	72	350	130
4"	101	101.2	113	300	180



Con Trama – Pivote de Riego – Negra

Manguera de PVC reforçada con hilos sintéticos utilizada en pivotes de riego. Ligero y flexible, posee buena resistencia a la abrasión e intemperie.

Temperatura de Trabajo: +5°C ~ +50°C (PVC).

DIÂMETRO NOMINAL	DIÂMETRO INTERIOR	DIÂMETRO EXTERIOR	VACÍO	RADIO DE CURVATURA	LARGO
pul.	mm	mm	mm	mmHg	25°C mm
1.1/4"	32	31.5	37.5	400	70
1.1/2"*	38	38	45.5	400	90
2.1/2"	65	62.5	72	350	130
4"	101	101.2	113	300	180



Braided – Irrigation Pivot – Black

Reinforced PVC hose with synthetic threads used in irrigation pivots. Lightweight and flexible, it has good resistance to abrasion and bad weather.

Working Temperature: +5°C ~ +50°C (PVC).

NOMINAL DIAMETER	INTERNAL DIAMETER	EXTERNAL DIAMETER	VACUUM	BEND RADIUS	LENGTH
inches	mm	mm	mm	mmHg	25°C mm
1.1/4"	32	31.5	37.5	400	70
1.1/2"*	38	38	45.5	400	90
2.1/2"	65	62.5	72	350	130
4"	101	101.2	113	300	180



Diâmetros marcados na cor cinza são fornecidas sob consulta